



LIGHT TOWER JLT SERIES



JLT 9EC MODEL Light Tower

Number and Power of Lamps	Optional 4x400W Metal Halide /4x200W Led/4x300W Led	
Luminous Flux (lm)	Total 104000/200000lm	
Lamp Model	E40/Led	
Lamp Type	Optional Metal Halide or LED	
Lamp Protection Grade	IP 65	
Mast	Optional 3-4-5-6 section	
Mast Driving Type	Mechanical	
Lifting Limit (mm)	Optional 5-7 mt	
Rotation Angle of the mast	Manuel	
Adjustable Angle	Standard is Fixed Type – 360° Optinal	
Generator Model	JDG 9500 EC – With Canopy	
Generator Type	Single Phase with Brush Alternator	
Engine Type	Single Cylinder, Vertical, 4 Stroke, Air Cooled Diesel	
Engine Speed (rpm)	3000	3600
Engine Starting System	Electric – Key Start	
Voltage	230 V	120 V/240 V
Rated Frequency	50 Hz	60 Hz
Insulation Class	F	
Rated Power (kVA)	7,5	8,5
Max. Power (kVA)	8,8	9,7
Output Socket	Single Phase Socket	
Fuel Tank Capacity (L)	30	
Fuel Tank Type	Upper Tank	
Continuous Running Time(hrs)	20	
Engine Oil	SAE 15W40/SAE 10W30	
Dry Weight (kg)	395	
Dimensions (LxMxH)	1600x1100x1550	
Wheel Model	185R14C	
Wheel Type	Rubber Type	
Support Leg Type	Hand Operated	

Features and Benefits

Easy Transport	Compact
Effective Using	Low Noice Level
Heavy Duty Design	Low Operating Cost
Durability	Global Technical Service and Maintenance Support



www.jcbenergy.es