



DIESEL PORTABLE GENERATORS

JPD SERIES



www.jcbenergy.es

DIESEL PORTABLE GENERATORS – JPD SERIES

GROUP		JPD 5000SP	JPD 7200SP	JPD 9000TP
Rated Output	KW	5/5,5	7,2/7,9	7,2/7,9
Rated Output	KVA	5/5,5	7,2/7,9	9/9,9
Frequency	Hz	50/60	50/60	50/60
Phase Number		Single Phase	Single Phase	Three Phase
Power Factor		1	1	0,8
Overall dimension	(L*W*H)(mm)	750*515*640	750*515*640	750*515*640
Net Weight	kg	119	128	126
Fuel Tank Capacity	L	12,5	16	16
Structure Type	h	Single cylinder, in-lined, 4 stroke, air cooled		
Noice dB(A) @ 7m		85	85	85
Bore x Stroke	mm	88 x 75	95 x 75	92 x 75
Displacement	ml	456	532	498
Fuel Consumptuin Rate	(g/ KW.h)	275	285	≤277
Rated Rotation Speed	rpm	3000	3000	3000
Starting System		12V Electric Starter	12V Electric Starter	12V Electric Starter
Insulation Grade		H	H	H
Continuous running time	h	8	8	8
Optinal		ATS/remote control/digital panel/wheel and handle		



www.jcbenergy.es